

## Premierbond 2PT • White

TWO-COMPONENT ADHESIVE DESIGNED FOR EASY APPLICATION AND FORMULATED FOR BONDING TO MOST SUBSTRATES BOTH INTERIOR AND EXTERIOR

## PRODUCT DESCRIPTION

Premierbond 2PT is a two-component polyurethane adhesive. The formulation has been designed to give ease of mixing for notched by scraper applications. This filled adhesive has been formulated for the bonding of U-PVC and GRP sheets to most building substrates, including brickwork, plaster, concrete, tiles, block work, etc.

## DIRECTIONS OF USE

Premierbond 2PT is supplied as a 6.5kg pack. The mix ratio is 12:1 by weight. Part A is contained in a bucket and part B in a sealed sachet, inside the bucket. Once mixed, the pot life is 20 minutes at 20°C (Longer at lower temperatures) and so substrate preparation should be complete before mixing.

Add all of the part B to the part A and stir until a uniform colour is achieved, ensuring that the sides are scraped down often during mixing. Mixing is best carried out using a 60mm paddle mixer on a drill. When mixed, apply the adhesive to one surface only.

Apply to sheet with a 6mm notched trowel and apply immediately to the substrate smoothing outwards from the centre. Flat plastered walls can have 4-5mm. Leave to cure for at least 4 to 6 hours before removing the protective film.



## CHARACTERISTICS / ADVANTAGES

- Shelf Life: 6 months
- Curing time: 4-6 hours (initial cure: 20 minutes)
- Full sheet coverage
- Less chance of bubbling
- Doesn't need moisture/temp to cure
- Tough, long lasting resilient bond

## PRODUCT INFORMATION

Base	Hybrid
Based on:	Part A: Paste approx 3850 poise Part B: Low viscosity liquid
2440 x 1220mm	Part A: 1.70 - 1.73 Part B: 1.21 - 1.23
Chemical resistance	Resistant to water, dilute acids and alkalis and aliphatic oils
Solvents	None
Flammability	N/A
Service temp.	-40°C to +130°C
Application temp.	Minimum +10°C ideally above 15°C Minimum +30°C ideally below 25°C
Storage life at 25°C	6 months in unopened containers. Store between 5°C and 25°C

# Premierbond 2PT • White

## SURFACE PREPARATIONS AND FINISHING

Surfaces must be clean, dry and free from any contaminants liable to impair adhesion. New build structures should be allowed to dry out for at least 6 weeks prior to application of Premierbond 2PT and should then have a moisture content on the surface and in the core of less than 14%. Very porous or dusty substrates may be sealed with a dilution of PVA. Ensure that the PVA is completely dried out.

All materials should be allowed to acclimatise for at least 24 hours before bonding. The sheet, air temperature, adhesive and substrate should all be close to the final operational temperature of the building prior to application to avoid thermal stresses from expansion of the plastic sheeting.

## CLEANING

Tools to be cleaned after use with water.

## LIMITATIONS

Premierbond 2PT will not bond to polyolefin plastics, e.g. polypropylene

## HEALTH & SAFETY

May produce an allergic reaction

Keep out of the reach of children

## PLEASE NOTE

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Oadby Plastics. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Oadby Plastics' written consent. The technical information in this document serves as an indication and is non-exhaustive. Oadby Plastics is not liable for any damage, either direct or indirect, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Oadby Plastics reserves the right to amend the wording of this document. Oadby Plastics cannot be held liable for any damage, either direct or indirect, due to the use of the product depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage. All deliveries are made exclusively in accordance with our terms and conditions.

# Premierbond 2PT • White

## PART A

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 | Product Identifier

**Trade name:** Premierbond 2PT

#### 1.2 | Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:**

Component for polyurethane systems

### SECTION 2: Hazards identification

#### 2.1 | Classification of the substance or mixture

**Classification under CLP:**

This product has no classification under CLP

#### 2.2 | Label elements

This product has no label elements

#### 2.3 | Other hazards

**PBT:**

This product is not identified as a PBT/vPvB substance

### SECTION 3: Composition/information on ingredients

#### 3.2 | Mixtures

**Contains:**

Hydroxylated polyols and non-reactive additives. Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels

### SECTION 4: First aid measures

#### 4.1 | Description of first aid measures

**Skin contact:**

Wash immediately with plenty of soap and water

**Eye contact:**

Bathe the eye with running water for 15 minutes. Seek medical attention if irritation persists

**Ingestion:**

Wash out mouth with water. Do not induce vomiting. Consult a doctor

**Inhalation:**

Move to fresh air. In the event of symptoms seek medical advice

# Premierbond 2PT • White

## SECTION 4: Continued

### 4.2 | Most important symptoms and effects, both acute and delayed

**Skin contact:**

There may be mild irritation at the site of contact

**Eye contact:**

There may be irritation and redness

**Ingestion:**

There may be irritation of the throat

**Inhalation:**

No symptoms

### 4.3 | Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:**

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1 | Extinguishing media

Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers

### 5.2 | Special hazards arising from the substance or mixture

**Exposure hazards:**

In combustion emits toxic fumes

### 5.3 | Advice for fire-fighters:

Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes

## SECTION 6: Accidental release measures

### 6.1 | Personal precautions, protective equipment and emergency procedures

**Personal precautions:**

Refer to section 8 of TDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid

### 6.2 | Environmental precautions:

Do not discharge into drains or rivers. Contain the spillage using bunding

### 6.3 | Methods and material for containment and cleaning up

**Clean-up procedures:**

Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method

### 6.4 | Reference to other sections:

Refer to section 8 of the TDS

# Premierbond 2PT • White

## SECTION 7: Handling and storage

### 7.1 | Precautions for safe handling

**Handling requirements:**

Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance. Protect against moisture

### 7.2 | Conditions for safe storage, including any incompatibilities

**Storage conditions:**

Keep container tightly closed. Recommended storage temperature: 15-25°C. Protect from frost/do not freeze. Avoid contact with water or humidity

### 7.3 | Specific end use(s)

No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 | Control parameters

**Workplace exposure limits:**

No data available

**DNEL/PNEC:**

No data available

### 8.2 | Exposure controls

**Respiratory protection:**

Respiratory protection not required

**Hand protection:**

Protective gloves

**Eye protection:**

Safety glasses. Ensure eye bath is to hand

**Skin protection:**

Protective clothing

## SECTION 9: Physical and chemical properties

### 9.1 | Information on basic physical and chemical properties

State	Liquid
Colour	Beige
Odour	Perceptible odour
Evaporation rate	Negligible
Oxidising	Non-oxidising (by EC criteria)
Solubility in water	Insoluble
Viscosity	Highly viscous
Boiling point/range °C	>195°C

## Premierbond 2PT • White

## SECTION 9: Continued

Melting point/range°C	No data available
Flammability limits %:	
Lower	No data available
Upper	No data available
Flash point°C	>185°C
Part.coeff. n-octanol/water	No data available
Autoflammability	No data available
Vapour pressure	3 hPa @ 20 Deg C
Relative density	1.72
VOC g/l	No data available

## 9.2 | Other information

No data available

## SECTION 10: Stability and reactivity

## 10.1 | Reactivity

Stable under recommended transport or storage conditions

## 10.2 | Chemical stability

Stable under normal conditions

## 10.3 | Possibility of hazardous reactions

Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below

## 10.4 | Conditions to avoid

Heat. Moist air. Humidity

## 10.5 | Incompatible materials

## Materials to avoid:

Strong oxidising agents. Strong acids

## 10.6 | Hazardous decomposition products

In combustion emits toxic fumes

# Premierbond 2PT • White

## SECTION 11: Toxicological information

### 11.1 | Information on toxicological effects

**Toxicity values:**

No data available

**Symptoms / route of exposure****Skin contact:**

There may be mild irritation at the site of contact

**Eye contact:**

There may be irritation and redness

**Ingestion:**

There may be irritation of the throat

**Inhalation:**

No symptoms

## SECTION 12: Ecological information

### 12.1 | Toxicity

**Exotoxicity values:**

No data available

### 12.2 | Persistence and degradability

No data available

### 12.3 | Bioaccumulative potential

No data available

### 12.4 | Mobility in soil

Insoluble in water

### 12.5 | Results of PBT and vPvB assessment

**PBT identification:**

This product is not identified as a PBT/vPvB substance

### 12.6 | Other adverse effects

Negligible ecotoxicity

## SECTION 13: Disposal considerations

### 13.1 | Waste treatment methods

**NB:**

The user's attention is drawn to the possible existence of regional or national regulations regarding disposal

# Premierbond 2PT • White

## SECTION 14: Transport information

### 14.1 | Transport class

This product does not require a classification for transport

## SECTION 15: Regulatory information

### 15.1 | Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:**

Not applicable

### 15.2 | Chemical Safety Assessment

A chemical safety assessment has not been carried out for the substance or the mixture by the supplier

## SECTION 16: Other information

### Other information

This technical data sheet is prepared in accordance with Commission Regulation (EU) No 2015/380

\*indicates text in the TDS which has changed since the last revision.

Depending on the production parameters, any uncovered surfaces of thermoset moldings produced using this raw material may contain traces of substances (e.g. starting and reaction products, catalysts, release agents) with hazardous characteristics. Skin contact with traces of these substances must be avoided. When demolding or otherwise handling freshly molded thermoset parts, protective textile gloves must be worn as a minimum

### Legal disclaimer

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Oadby Plastics shall not be held liable for any damage resulting from handling or from contact with the above product.



## Premierbond 2PT • White

## PART B

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1 | Product Identifier

Trade name: Premierbond 2PT

## 1.2 | Relevant identified uses of the substance or mixture and uses advised against

## Use of substance / mixture:

Di-/polyisocyanate components for the production of polyurethanes

## SECTION 2: Hazards identification

## 2.1 | Classification of the substance or mixture

## Classification under CLP:

Eye Irrit. H319; Acute Tox. 4: H332; Carc. 2: H351; Resp. Sense. 1: H334, Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 3: H335; -: EUH204

## Most important adverse effects:

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Contains isocyanates. May produce an allergic reaction

## 2.2 | Label elements

## Hazard statements:

H315: Causes skin irritation  
H317: May cause an allergic skin reaction  
H319: Causes serious eye irritation  
H332: Harmful if inhaled  
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled  
H335: May cause respiratory irritation  
H351: Suspected of causing cancer  
H373: May cause damage to organs through prolonged or repeated exposure  
EU204: Contains isocyanates. May produce an allergic reaction

## Hazard pictograms:

GHS07: Exclamation mark  
GHS08: Health hazard



## Signal words:

Danger

## Precautionary statements:

P260: Do not breathe dust/fumes/gas/mist/vapours/spray  
P280: Wear protective gloves/protective clothing/eye protection/face protection  
P302+352: IF ON SKIN: Wash with plenty of water/soap  
P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P312: Call a POISON CENTER / doctor if you feel unwell.

## Premierbond 2PT • White

## SECTION 2: Continued

## 2.3 | Other hazards:

Danger of serious damage to health by prolonged exposure

**PBT:**

This product is not identified as a PBT/vPvB substance

## SECTION 3: Composition/information on ingredients

## 2.3 | Mixtures

**Hazardous ingredients:**

DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES) - REACH registered number(s): EXEMPT - REACH POLYMER

EINECS	CAS	PBT/WEL	CLP Classification	Percent
-	9016-87-9	-	Carc. 2: H351; Acute Tox. 4: H332; STOT RE 2: H373; Eye Irrit. 2: H319; STOT RE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	>90%

## SECTION 4: First aid measures

## 4.1 | Description of first aid measures

**Skin contact:**

Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap

**Eye contact:**

Bathe the eye with running water for 15 minutes. Consult a doctor

**Ingestion:**

Wash out mouth with water. Do not induce vomiting. Consult a doctor

**Inhalation:**

Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor

## 4.2 | Most important symptoms and effects, both acute and delayed

**Skin contact:**

There may be irritation and redness at the site of contact. An itchy rash may occur at the site of contact

**Eye contact:**

There may be irritation and redness. The eyes may water profusely

**Ingestion:**

There may be soreness and redness of the mouth and throat

**Inhalation:**

There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing. Harmful by inhalation

## 4.3 | Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:**

Eye bathing equipment should be available on the premises

# Premierbond 2PT • White

## SECTION 5: Fire-fighting measures

### 5.1 | Extinguishing media

Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers

### 5.2 | Special hazards arising from the substances or mixtures

#### Exposure hazards:

In combustion emits toxic fumes

### 5.3 | Advice for fire-fighters

Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes

## SECTION 6: Accidental release measures

### 6.1 | Personal precautions, protective equipment and emergency procedures

#### Personal precautions:

Refer to section 8 of the TDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid

### 6.2 | Environmental precautions

Do not discharge into drains or rivers. Contains the spillage using bonding

### 6.3 | Methods and material for containment and cleaning up

#### Clean-up procedures:

Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method

### 6.4 | Reference to other sections

Refer to section 8 of TDS

## SECTION 7: Handling and storage

### 7.1 | Precautions for safe handling

#### Handling requirements:

Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air

### 7.2 | Conditions for safe storage, including and incompatibilities

#### Storage conditions:

Keep container tightly closed. Recommended storage temperature: 15-25°C. Protect from frost/do not freeze. Avoid contact with water or humidity

### 7.3 | Specific end use(s)

No further relevant information available

## Premierbond 2PT • White

## SECTION 8: Exposure controls/personal protection

## 8.1 | Control parameters

## Hazardous ingredients:

DIPHENYLEMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES)

## Workplace exposure limits:

## Respirable dust

State	8 hour TWA	15 min. STEL	CLP Classification	Percent
UK	0.02 mg/m <sup>3</sup>	0.07 mg/m <sup>3</sup>	-	-

## DNEL / PNEC:

No data available

## 8.2 | Exposure controls

## Engineering measures:

Ensure there is sufficient ventilation of the area

## Respiratory protection:

Self-contained breathing apparatus must be available in case of emergency

## Hand protection:

Protective gloves

## Eye protection:

Safety glasses. Ensure eye bath is to hand

## Skin protection:

Protective clothing

## SECTION 9: Physical and chemical properties

## 9.1 | Information on basic physical and chemical properties

State	Liquid
Colour	Brown
Odour	Perceptible odour
Evaporation rate	Negligible
Oxidising	Non-oxidising (by EC criteria)
Solubility in water	Insoluble
Viscosity	Oily
Boiling point/range°C	330°C
Melting point/range°C	No data available
Flammability limits %: lower	No data available
Upper	No data available
Flash point°C	>204°C
Part.coeff. n-octanol/water	No data available

## Premierbond 2PT • White

## SECTION 9: Continued

9.1   Autoflammability°C	>500°C
Relative density	1.23
pH	N/A
VOC g/l	No data available

## 9.2 | Other information

No data available

## SECTION 10: Stability and reactivity

## 10.1 | Reactivity

Stable under recommended transport or storage conditions

## 10.2 | Chemical stability

Stable under normal conditions

## 10.3 | Possibility of hazardous reactions

**Hazardous reactions:**

Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below

## 10.4 | Conditions to avoid

Heat. Moist air. Humidity

## 10.5 | Incompatible materials

**Materials to avoid:**

Strong oxidising agents. Strong acids. Alcohols. Amines. Water. On contact with water, gaseous decomposition products are formed, which cause build-up of pressure in tightly closed containers. Risk of bursting. Reacts with substances which contain active hydrogen

## 10.6 | Hazardous decomposition products

In combustion emits toxic fumes

## Premierbond 2PT • White

## SECTION 11: Toxicological information

## 11.1 | Information on toxicological effects

## Hazardous ingredients:

## DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES)

ORL	RAT	LD50	49	gm/kg
SKN	RBT	LD50	>9400	mg/kg

## Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	INH DRM	Hazardous: calculated
Carcinogenicity	-	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

## Symptoms / routes of exposure

## Skin contact:

There may be irritation and redness at the site of contact. An itchy rash may occur at the site of contact

## Eye contact:

There may be irritation and redness. The eyes may water profusely

## Ingestion:

There may be soreness and redness of the mouth and throat

## Inhalation:

There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing wheezing.  
Harmful by inhalation

## Premierbond 2PT • White

## SECTION 12: Ecological information

## 12.1 | Toxicity

**Ecotoxicity values:**

No data available

## 12.2 | Persistence and degradability

No data available

## 12.3 | Bioaccumulative potential

No data available

## 12.4 | Mobility in soil

Insoluble in water

## 12.5 | Results of PBT and vPvB assessment

**PBT identification:**

This product is not identified as a PBT/vPvB substance

## 12.6 | Other adverse effects

Negligible exotoxicity

## SECTION 13: Disposal considerations

## 13.1 | Waste treatment methods

**Disposal operations:**

Transfer to a suitable container and arrange for collection by specialised disposal company

**Waste code number:**

07 02 08

**NB:**

The user's attention is drawn to the possible existence of regional or national regulations regarding disposal

## SECTION 14: Transport information

**Transport class**

This product does not require a classification for transport

## SECTION 15: Regulatory information

## 15.1 | Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:**

Not applicable

## 15.2 | Chemical Safety Assessment

A chemical safety assessment has not been carried out for the substance or the mixture by the supplier

## Premierbond 2PT • White

## SECTION 16: Other information

**Other information**

This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830

\*Indicates text in the TDS which has changed since the last revision

**Phrases used in s.2 and s.3**

EUH204: Contains isocyanates. May produce an allergic reaction

H315: Causes skin irritation

H317: May cause an allergic skin reaction

H319: Causes serious eye irritation

H332: Harmful if inhaled

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335: May cause respiratory irritation

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>

**Legal disclaimer**

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide.

Oadby Plastics shall not be held liable for any damage resulting from handling or from contact with the above product